

MOLDED PANEL HOLLOW CORE



| | |
|---------------------------|--|
| Specifications: | 3 Ply construction. Meets or exceeds industry standards of WDMA I.S.1. |
| Lay Up Method | Loose |
| Maximum Sizes: | Width - 3/0 Length - 8/0 *Certain styles only* |
| Thickness: | 1-3/8" and 1-3/4" ONLY |
| Stiles: | MDF on only 1-3/8" Thickness & 6/8 Length. FJ Softwood option on 1-3/8" and 1-3/4" Thickness, to 8/0 length. Width = 1" Nominal, 13/16" Minimum after prefit size. |
| Rails: | 1-3/8" Thickness = MDF, 1-5/8" Nominal, 1" Minimum after undercut 1-3/4" Thickness = MDF, 2-1/4" Nominal, 1" Minimum after undercut 2" Nominal Bottom rail available on 1-3/8" Thickness (DBR) |
| Core: | Cellular Honeycomb build up pads. |
| Lock Blocks: | Double 3" x 10" Particleboard (28lb) as standard. |
| Faces: | Primed MDF Molded Panel, Single ply |
| Adhesive: | Type-1 PVA, Interior installation only. |
| Machining: | To Specification |
| Lites: | N/A |
| Louvers: | N/A |
| Acoustical Rating: | N/A |
| Warranty: | Standard two year. See limited warranty for details. *No warranty for Telegraphing* |
| Description | (FP-1-3/8) = 1-3/8" Thick, MDF Stiles |
| Abbreviations: | (FJ-1-3/8) = 1-3/8" Thick, FJ Softwood Stiles (FJ-1-3/4) = 1-3/4" Thick, FJ Softwood Stiles |
| Recommended Use: | Residential and Light Commercial |

02

*See molded skin selection guide for all panel elevation designs.