ABS-AC "E" FRAME DOO	OR W/ INTEGE	☐ MITE	R TRIM	NOTCH .	JAMBS (HEADER RES			
(THROAT SIZE)	•] ————————————————————————————————————	TO TOP	ARE CUT TRIM	NOTCH	HEADS (HEADER CU	T NET BETWE	EN JAMBS)	
HINGE: X	(•)_							
TRIM: 1" STANDARD								
FRAME FINISH: CLR BL DK BRZ PT								
DOOR FRAME SEAL: GREY BLACK								
SCRIBE: YES 1" 2" NO 1-1/2" INTUMESCENT IN YES								
JAMBS (CONCEALED): NO GLASS 1/4" 1/2"			FLOOR LINE	!				
THICKNESS: 3/8" GLAZING BEAD GRY COLOR:: BLK			SCRIBE ROUGH	L OPENING SIZE	_j =X			
INSTALLATION: CLIPS SCREWRACE		NOTE: FOR VERTICAL OR HORIZONTAL MULLIONS, OR SPECIAL ELEVATION,						
SIDELITE STRIKE SIDE ORIENTATION: HINGE SIDE		Р	ROVIDE DRAWI					
SPECIFIC DOO!	R FRAME 1	CLOSER L	ABEL	K FRAMES BY	NUMBER \ SPEC	IAL PACK	AGING	
NUMBER SWING WIDTH (IN)	HEIGHT (IN)		NUTES NEUT.					
DOORNERICA	SAL	ES ORI	DER AND	FIELD	MEASUR	EMEN	NT	
ABS - Architectural Components					JOB NAME :			
8401 Rovana Cir. Sacramento CA. 95828 Toll Free Number: (866) 566-2161 Phone Main: (916) 388-2161 Fax: (916) 388-9336	ABS-AC FORM P.O. NUN	/IBER :				PAGE	OF	